

CLASS Q - 1

TRACTOR & TRUCK PULL

Thursday, July 24, 2014 at 7.00 p.m.

Brett Neeley, Superintendents
618-562-0613

Weigh - in at Fairground from 5:00 - 7:00 P.M.

Driver and one helper will receive a pit pass upon registration

1st place trophy; 2nd thru 8th, Rosette

IPA PRO STOCK 4X4 TRUCK

Premium Offered \$1,600.00

Entry Fee - \$20.00

1st, \$425.00; 2nd, \$325.00; 3rd, \$225.00; 4th, \$175.00;
5th, \$150.00; 6th, \$125.00; 7th, \$100.00; 8th, \$75.00;

3001. IPA Pro Stock 4X4 Truck

IPA N/A FARM TRACTOR

Premium Offered \$1,200.00

Entry Fee \$20.00

1st, 300.00; 2nd, \$180.00; 3rd, \$160.00; 4th, \$130.00
5th, \$115.00; 6th, 90.00; 7th, \$75.00; 8th, \$60.00; 9th, \$50.00; 10th, \$40.00

3002. IPA N/A Farm Tractor

IPA LIGHT SUPER STOCK TRACTOR

Premium Offered \$2,000.00

Entry Fee - \$20.00

1st, 525.00; 2nd, \$400.00; 3rd, \$350.00; 4th, \$275.00;
5th, \$200.00; 6th, \$125.00; 7th, \$75.00; 8th, \$50.00

3003. IPA Pro Farm Tractor

IPA MINI RODS

Premium Offered \$1,400.00

Entry Fee \$20.00

1st, \$400.00; 2nd, \$300.00; 3rd, \$200.00; 4th, \$150.00;
5th, \$125.00; 6th, \$100.00; 7th, \$75.00; 8th, \$50.00

3004. IPA Mini Rods

8000lb MODIFIED DIESEL TRUCK CLASS

Premium Offered \$780.00

Entry Fee \$20.00

Scales at Fairgrounds - Weigh-in 5-7p.m.

1st, \$225.00; 2nd, \$185.00; 3rd, \$135.00; 4th, \$100.00;
5th, \$85.00; 6th, \$50.00

3005. 8000lb Modified Diesel Truck

Rules and Regulations:

Exhaust must exit down under the truck or up in the bed (no holes in the hood)

Open exhaust permitted.

Hitch Point must be the maximum of 42 inches from the center of the rear axle. The hitch cannot connect to the axle in any way. Hitch pivot point cannot be in the front of the axle centerline. The hitch must be accessible and rigid. No floating hitches.

D.O.T tires only, maximum 35" inch diameter (no barred or cut tire allowed)

All trucks must have drive shaft loops and shields.

Hitch height 26" inch maximum (4wd)

Front weights are allowed must be secure Lost of weight will be cause for disqualification
No fuel tanks or batteries allowed the in cab expect factory located.

No sanctioned trucks or pulling club trucks allowed Diesel

DIESEL TRUCK RULES

1. Maximum Turbo inlet of 2.8" inch (1)- single

turbo only allowed.

2. Stock injection pump
3. No water injection allowed
4. Radiator must be in the stock location and be original.
5. One ton or smaller driveline, OEM transfer case and transmission
6. Must use diesel road fuel, no fuel cell or no water injection allowed.
7. Stock type suspension only, Ladder Bars and Stops allowed.
8. The air cleaner must be in stock location no holes in the hood.

GENERAL RULES

1. All driver must be at least 16 years of age, and if under 18 must have parents written permission (or guardian).
2. No alcoholic beverages
2. Same truck can only run once in the same class.
3. Judge has the option to inspect any entry at anytime.
4. Hitching device MUST HAVE a MINIMUM OF 3" INCH DIAMETER OPENING and be behind the rear portion of the body. All clevis made of a minimum of 3/4" diameter.
5. Any pulling vehicle that runs and or skids out of bounds will be disqualified.
6. No pressurized containers, no nitrous oxide or nitro based fuels. No alcohol. No propane or butane on diesel engine. No water injection systems allowed. No unsafe fuels.
7. Any weight loss of weight while hooked to the sled, Will be cause for disqualification.
8. Dual wheel trucks one (1) ton or less allowed.
9. JUDGES DECISIONS ARE FINAL AND TAKE PRECEDENT OVER ALL PRINTED MATERIAL

Batteries:

1. The batteries must be securely mounted. They may not be located in the driver

compartment.

Body:

1. The body must be the OEM truck body, including the full bed floor. The body must retain full sheet metal. Metal after-market hoods are permitted. Fiberglass is prohibited.

Batteries:

1. The batteries must be securely mounted. They may not be located in the driver compartment.

Body:

1. The body must be the OEM truck body, including the full bed floor. The body must retain full sheet metal. Metal after-market hoods are permitted. Fiberglass is prohibited.

Brakes:

1. Four-wheel hydraulic brakes are mandatory.

Chassis:

1. The OEM chassis is mandatory. The engine must be in the OEM location for the body used. The vehicle must retain the full OEM chassis. Wheel tubs, back-half conversions, tube chassis etc., are prohibited.

Cooling System:

1. Radiators must be in the stock location and be at least stock size.

Credentials:

1. All drivers must have a valid state driver's license.

Driveline:

1. An OEM transmission and transfer case is mandatory. It must have been an option on a one-ton or smaller pickup.

Driver Restraint System:

1. The OEM restraint system is mandatory and must be worn.

Engine:

1. The engine is limited to a stock-appearing, OEM make-specific compression ignition engine.

Exhaust:

1. All vehicles must be equipped to direct

exhaust upward or downward. The exhaust must exit rearward of the driver's compartment. Stacks exiting through the hood or fender well are prohibited. Two 3/8 inch diameter bolts must be placed through the exhaust pipe in a cross pattern within one inch of each other as close to the turbo as is practical.

Fire Extinguisher System:

1. A fire extinguisher system is permitted. It must be securely mounted.

Fuel:

1. The fuel must be pump #1, #2 diesel only. Soy/Biodiesel fuel is permitted. Off-road diesel fuel is prohibited.

Fuel Injection Pump:

1. The fuel injection pump is limited to a stock-appearing, OEM engine model-specific pump only. Pumps from different years in the same engine model may be interchanged.

Fuel System:

1. The OEM fuel tank is mandatory and must be used. Racing fuel cells are prohibited and must be removed from the vehicle.

Hitch:

1. The hitch must be a "Reese"-style hitch; reinforcements are permitted. Trick hitched are prohibited. The hooking point must be the rear-most point on the vehicle and must be rearward of the stock location of the tailgate. The hitch must be horizontal to the ground and stationary in all directions. Bumpers may be notched or removed. The hitch's height from the ground may not exceed 26 inches. The hooking point must a minimum 3.00 inch diameter opening for the sled hook. The hooking point will be measured to the center of the clevis loop.

Interior:

1. A complete interior, including dashboard, door panels, headliner, etc., is mandatory. Two matching front seats are mandatory. After market seats are permitted; they must be fully

upholstered. All factory controls (lights, signals, horn, windows, wipers, etc.) must be retained and operative.

Nitrous Oxide:

1. Nitrous oxide is prohibited. No other oxygen extenders are allowed. All system components must be removed from the truck.

Propane:

1. Propane is prohibited. All system components must be removed from the truck.

Rear End:

1. Non-OEM rear-end housings are prohibited. It must have been an option on a one-ton or smaller pick up. Rear axle bolts must be covered by a cap or shield. For class MH/E, the rear end must be the model supplied with the vehicle as manufactured.

Street Equipment:

1. Complete headlight and taillight assemblies (all) are mandatory and must be operative. Complete OEM windshield and windows are mandatory. Windows must be operative per factory specifications; that is, they must open and close via OEM electrical or mechanical means.

Suspension, Front:

1. The upper mounting point for strut assemblies must be in the factory location. Adjustable caster/camber pillow ball mounts are permitted. The lower control arm may be strengthened provided factory-mounting points to chassis are maintained. The lower mounting point for the strut assembly may be modified for improved caster or camber. Strut tower braces, lower tie bars, sway bars, and limit straps are permitted. Traction bars and devices are permitted.

Suspension, Rear:

1. An OEM-style suspension is mandatory. Lowering or raising the vehicle height with suspension modifications is permitted. Traction bars and devices are permitted; they must be

bolt-on only; welds are permitted for attachment to frame or axle housing. Control arms may be strengthened or replaced, provided all original mounting points are retained. Strut tower braces, lower tie bars, sway bars, limit straps, and camber kits are permitted. The rear suspension must maintain a minimum shock travel of one inch. All rear suspensions must use at least one working shock absorber per wheel.

Tow Vehicles:

1. Tow vehicles are prohibited.

Transfer Case:

1. Non-OEM transfer cases are prohibited. The transfer case must have been an option on a one-ton or smaller pick up truck.

Transmission, Automatic:

1. Non-OEM transmissions are prohibited. Aftermarket torque converters, valve bodies and internal components are permitted. Transmission brakes are prohibited. Any non-OEM floor-mounted automatic transmission shifter must be equipped with a spring-loaded positive reverse lockout device to prevent the shifter from accidentally being put into reverse gear. A functional neutral safety switch is mandatory. All transmission lines must be metallic or high-pressure-type hose. All vehicles with engines running 4500 RPM or more and using an automatic transmission must be equipped with a transmission shield meeting SFI Spec 4.1 and must be labeled accordingly. A blanket-type shield is permitted; it must be appropriately labeled as meeting SFI Spec 4.1 and it must extend from the rear of the block to the front of tail housing with a minimum six inch overlap where it is fastened. All non-blanket-type shields must incorporate two (or one, per manufacturer's instructions) 3/4 inch by 1/8 inch straps that bolt to the shield on each side and pass under the transmission pan unless the transmission pan is labeled as

meeting SFI Spec 4.1. If vehicles with engines running 4500 RPM or more and using an automatic transmission must be equipped with a flex plate meeting SFI Spec 29.1 and be covered by a flex plate shield meeting SFI Spec 30.1.

Transmission, Manual:

1. Non-OEM transmissions are prohibited. Aftermarket internal components are permitted. A clutch meeting minimum SFI Spec 1.1 or 1.2 is mandatory on all vehicles with engines running 4500 RPM or more. All manual transmissions must be clutch assisted. Sequential shifters are prohibited. All vehicles with engines running 4500 RPM or more and equipped with a manual transmission must have a flywheel shield labeled as meeting minimum SFI Spec 6.3 or greater. Applications for which an SFI Spec flywheel shield is not available may use a properly attached SFI 4.1 or 4.2 blanket that completely covers the bellhousing; it must be attached to the block and extend rearward to the transmission with a minimum six inch overlap where it is fastened.

Water Injection:

1. Water injection is prohibited. All system components must be removed from the truck.

Wheelbase:

1. The vehicle must retain the original factory wheelbase and track width.

CONTEST TO BE GOVERNED BY JUDGES

ALL DECISIONS FINAL

NOT RESPONSIBLE IN CASE OF ACCIDENT